

High-performance and robust

The medium quadros

- Integrated trolley takes rough ground in its stride with large wheels with wide solid rubber tyres
- Integrated hose drum with foldable crank
- 7.5 m power lead with cable reel (599 TS T: 5 m)
- Dirtkiller lance with stainless steel pipe, stainless steel lance with flat jet nozzle
- Storage for trigger gun with safety catch and lances
- Shock absorbing buffers, front and rear
- Total-Stop system with delayed motor cut-out
- Additional electrical over-current protection
- Water tank
- High pressure detergent
- Parking brake





Technical specifications	quadro 599 TS T	quadro 799 TS T	quadro 899 TS T
Ord. no.	40,431	40,432	40,434
Operating pressure, continuously adjustable	30-150 bar / 3-15 MPa	30-180 bar / 3-18 MPa	30-150 bar / 3-15 MPa
Max. admissible overpressure	165 bar / 16.5 MPa	200 bar / 20 MPa	170 bar / 17 MPa
Water output	10 l/min (600 l/h)	13 l/min (780 l/h)	15 l/min (900 l/h)
Volume water tank	10 l	10 l	10 l
Motor speed	1.400 rpm	1.400 rpm	1.400 rpm
Connected load	230 V, 14 A, 50 Hz	400 V, 8.5 A, 50 Hz	400 V, 8.5 A, 50 Hz
Power intake / Power output	3.3 kW / 2.4 kW	5.5 kW / 4.0 kW	5.5 kW / 4.0 kW
Weight	62 kg	62 kg	62 kg
Features & Equipment	Ord. no.	Ord. no.	Ord. no.
Steel braided high-pressure hose	20 m NW 6 (43,416 1)	20 m NW 6 (43,416 1)	15 m NW 8 (44,879)
Tigger gun with safety catch M2000	(12,480)	(12,480)	(12,480)
Dirtkiller lance with stainless steel pipe	(46,150)	(46,150 1)	(46,150 2)
Stainless steel lance with flat jet nozzle	(12,392 2-M20035)	(12,392 2-M20045)	(12,392 2-D2506)